


No active tr.

DELPHION**Select CR****St****RESEARCH****PRODUCTS****INSIDE DELPHION****Log Out** **Work Files** **Saved Searches****My Account****Search:** Quick/Number Boolean Advanced Der

The Delphion Integrated View

Buy Now: ☒ **PDF** | [File History](#) | [Other choices](#)**Tools:** Add to Work File: [Create new Work File](#)**View:** [INPADOC](#) | **Jump to:** [Top](#)**Go to:** [Derwent](#) [Ema](#)**Title:** **JP10237362A2: ELECTRODEPOSITION COATING MATERIAL AND ELECTRODEPOSITION COATING****Derwent Title:** Electrodeposition coating - contains an aqueous colloidal solution dispersing inorganic oxide colloidal particles containing an antimicrobial metal component and an anionic electrodeposition coating [\[Derwent Record\]](#)**Country:** JP Japan**Kind:** A**Inventor:** KINO KATSUHIRO;
TANAKA ATSUSHI;**Assignee:** CATALYSTS & CHEM IND CO LTD
[News, Profiles, Stocks and More about this company](#)**Published / Filed:** 1998-09-08 / 1997-02-26**Application Number:** JP1997000058479**IPC Code:** Advanced: [A01N 59/16](#); [B05D 5/00](#); [B05D 7/24](#); [C09D 5/14](#); [C09D 5/44](#); [C25D 13/10](#);
Core: more...
IPC-7: [A01N 59/16](#); [B05D 5/00](#); [B05D 7/24](#); [C09D 5/14](#); [C09D 5/44](#); [C25D 13/10](#);**Priority Number:** 1997-02-26 JP1997000058479**Abstract:** PROBLEM TO BE SOLVED: To obtain an electrodeposition coating material capable of imparting a long-term excellent antimicrobial properties to a coating surface of a conductor material, and further forming a coating membrane excellent in appearance and adhesion, and useful for antimicrobial coating of a building material, fittings, etc., by adding an aqueous colloid solution of a specific antimicrobial inorganic oxide to a specified electrodeposition coating material.SOLUTION: This electrodeposition coating material comprises (A) an aqueous colloid solution dispersing inorganic oxide colloid particles such as silica, alumina, titania and a composite oxide thereof, containing an antimicrobial metal component such as silver, copper and zinc [e.g. the one having $\leq 500\text{nm}$ average particle diameter and 0.05-25wt.% antimicrobial metal component content in terms of oxide] and (B) anion type electrodeposition coating material, and is regulated so that the ζ -potential of the colloid particles in the component A may be $\leq -2\text{mV}$ within a pH range of 7.0-9.0 of the component A. The coating material preferably contains 0.1-20wt.% component B in the component A.

COPYRIGHT: (C)1998,JPO




Family: None

Other Abstract Info: CHEMABS 129(19)246616C CAN129(19)246616C [DERABS C98-537693](#)
[DERC98-537693](#)



[Nominate this for the Gallery...](#)



Copyright © 1997-2008 The Tho

[Subscriptions](#) | [Web Seminars](#) | [Privacy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact U](#)